#### TECHNICAL CHARACTERISTICS

Max 3.650   Max 3.650   Max 6.650   Max	SYSTEM SPECIFICATIONS	MF222 <sup>plus</sup>	MF282 <sup>plus</sup>	MF362 <sup>plus</sup>	MF452 <sup>plus</sup>	MF552 <sup>plus</sup>	
Paper-out capacity	Paper-in capacity	Standard: 1.150 Max: 3.650	Standard: 1.150 Max: 3.650	Standard: 1.150 Max: 3.650	Standard: 1.150 Max: 6.650	Standard: 1.150 Max: 6.650	
Monthly copy/print   80.000 pages   10.000 pages   125.000 pages   150.000 pages   20.000 pages   20.0000 pages   20.00000 pages   20.0000 pages   20.0000 pages   20.0000 pages   20.0000 pages   20.00000 pages   20.000000 pages   20.000000 pages   20.0000000000000000000000000000000000	Paper-out capacity						
Compage   Comp		<u> </u>			150.000 pages	200.000 pages	
Black toner duration	, , , ,	, , , , , , , , , , , , , , , , , , ,					
Up to 25.000 pages   Up to 25.000 pages   Up to 25.000 pages   Up to 26.000 pages   Up to 2	<u> </u>	Up to 27.000 pages	Up to 27.000 pages	Up to 27.000 pages	Up to 27.500 pages	Up to 27.500 pages	
Up to 120.000 pages	CMY toner duration						
(Drum)   (	Duration black images unit		1 1 2	1 1 3	1 1 2	1 1 3	
Cipeveloper	- a. a		1		, , ,		
Cloevelopen   Clorum		Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	Up to600.000 pages	Up to 600.000 pages	
Up to \$5.000 pages		(Developer)			(Developer)		
(Prum) (Drum) (D	Duration CMY images unit						
Cleveloper   Cle	<b>-</b>						
(Developer)		Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	Up to 600.000 pages	
System dimensions (Wx0xH)         615 x 685 x 779 mm         615 x 685 x 921 mm         650 x 685 x 828 x 921 mm			1 1 3				
Weight         Approximately 85 kg         Approximately 85 kg         Approximately 85 kg         Approximately 101 kg	System dimensions (WxDxH)	<u> </u>			<u> </u>		
Automatic duplex AS-SRA3, 52-256 gm² System memory 2.048 Mb Hard disk Z50 Gb Interface 10-Base-T / 100-Base-T / 1.000-Base-T Ethernet, USB 2.0 Network protocol TCPI/P (Phy 4 [PbG), [PX/SPX, NetBEU], AppleTalk (EtherTalk), SMB, LPD, IPP, SNMP, HTTP Paper format A6-SRA3, personalised paper format, banner paper max. 1.200 x 297 mm Paper weight S2-300 gm² Consumption PRINTER Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi CPU Type controller 800 Mhz Page description language Operating system Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintsh 0 SX 10.0, Lunix/Lunx/Citrix B80 X PCL Latin, 137x PostScript 3, Emulation Latin Print functions Direct printing PCL, PS, TIFE, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX) "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER Scan speed Up to 80 opm Up to 80 opm Up to 80 opm (optional) (o		Approximately 85 kg	Approximately 85 kg	Approximately 85 kg	Approximately 101 kg	Approximately 101 kg	
System memory   2.048 Mb			111 1 111 1 1	111 2 227 3	171	111 1111 1111	
Hard disk  250 Gb Interface  10-Base-T / 100-Base-T / 100-Base-T / 1.000-Base-T Ethernet, USB 2.0 Network protocol  TCP/IP (IPV4 / IPV6), IPX/SPX, NetBEUI, AppleTalk (EtherTalk), SMB, LPD, IPP, SNMP, HTTP Paper format  A6-SRA3, personalised paper format, banner paper max. 1.200 x 297 mm Paper weight  52-300 gm² Paper weight  52-300 gm² 220-240V / 50/60 Hz Max 1.5 kW (system) Consumption  PRINTER Print resolution  1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi CPU Type controller  800 Mhz Page description language Operating system  Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix Print fonts  80x PCL Latin, 137x PoStScript 3, Emulation Latin Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX) "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  SCANNER  SCANNER  SCAN door join loo originals  Up to 80 opm Up to 80 opm/160 ipm Up to							
Network protocol TCP/IP (IPv4 / IPv6), IPX/SPX, NetBEUI, AppleTalk (EtherTalk), SMB, LPD, IPP, SNMP, HTTP Paper format A6-SRA3, personalised paper format, banner paper max. 1.200 x 297 mm Paper weight 52-300 gm² Power absorption/ 220-240V / 50/60 Hz Max 1.5 kW (system)  PRINTER Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi CPU Type controller 800 Mhz Page description anguage  Departing system Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix Print fonts 80x PCL Latin, 137x PostScript 3, Emulation Latin Print functions Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX) "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER Scan speed Up to 80 opm Up to 80 opm Up to 80 opm - (optional) (option	•						
Network protocol TCP/IP (IPv4 / IPv6), IPX/SPX, NetBEUI, AppleTalik (EtherTalk), SMB, LPD, IPP, SNMP, HTTP Paper format A6-SRA3, personalised paper format, banner paper max. 1.200 x 297 mm Paper weight 52-300 gm² Power absorption/ consumption  PRINTER Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi CPU Type controller 800 Mhz Page description anguage  Operating system Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix Print fonts 80x PCL Latin, 137x PostScript 3, Emulation Latin Print functions Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX) "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER Scan speed Up to 80 opm Up to 80 opm Up to 80 opm	Interface		1.000-Base-T Ethernet, US	5B 2.0			
Paper format A6-SRA3, personalised paper format, banner paper max. 1.200 x 297 mm Paper weight 52-300 gm² Power absorption/ consumption  PRINTER Print resolution PCL 6c (XL3.0), PCL 5c, Post Script 3 (CPSI 3016), XPS anguage Departing system Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix Print fonts 80x PCL Latin, 137x PostScript 3, Emulation Latin Print functions Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX) "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER Scan speed Up to 80 opm Up to 80 opm Up to 80 opm Up to 80 opm Up to 80 opm/160 ipm							
Paper weight 52-300 gm² 220-240V / 50/60 Hz Max 1.5 kW (system) consumption  PRINTER  Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi  CPU Type controller 800 Mhz Page description anguage  Operating system Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix Macintosh OS X 10.x, Unix/Linux/Citrix Print fonts 80x PCL Latin, 137x PostScript 3, Emulation Latin Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX) "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER Scan speed Up to 80 opm Up to 80 opm Up to 80 opm (optional) (optional) (optional) R-ADF (300 dpi) 100 originals 100 originals 100 originals 100 originals  SCan speed Up to 80 opm/160 ipm Up to 80 op	•						
Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi Print resolution PCL 6c (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS anguage Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix Macintosh OS	•						
PRINTER Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi  CPU Type controller 800 Mhz Page description language PCL 6c (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS language  Operating system Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix  Print fonts 80x PCL Latin, 137x PostScript 3, Emulation Latin  Print functions Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)  "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  SCANNER  (B/W and colour) (optional) (optional) (optional)  R-ADF (300 dpi) 100 originals 100 originals 100 originals 100 originals  SCANNER (B/W and colour) (optional) (optional) (optional) (optional) (standard) (standard)  Dual scan speed Up to 80 opm/160 ipm							
PRINTER Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi  CPU Type controller 800 Mhz Page description   PCL 6c (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS   language   Operating system   Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix   Print fonts   80x PCL Latin, 137x PostScript 3, Emulation Latin   Print functions   Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)   "Easy Set" job planning, superimposition, watermark, copy protection    SCANNER   Soan speed   Up to 80 opm   Up to 80 opm   up to 80 opm   c			(-),				
Print resolution 1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi  CPU Type controller 800 Mhz  PCL 6c (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS  language  Operating system Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix  Print fonts 80x PCL Latin, 137x PostScript 3, Emulation Latin  Print functions Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX) "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed Up to 80 opm Up to 80 opm Up to 80 opm							
Page description   PCL 6c (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS	PRINTER						
Page description language  Operating system  Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix  Print fonts  80x PCL Latin, 137x PostScript 3, Emulation Latin  Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)  "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed  Up to 80 opm Up to 80 opm Up to 80 opm Up to 80 opm Optional) (optional) (optional)  (optional)  (optional)  (optional) (optional	Print resolution	1.800 equivalent x 600 dpi, 1.200 x 1.200 dpi					
Operating system  Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix  Print fonts  80x PCL Latin, 137x PostScript 3, Emulation Latin  Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)  "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed  Up to 80 opm Up to 80 opm/160 ipm Up to	CPU Type controller						
Windows XP 32/64bit, Windows VISTA 32/64bit, Windows 7 32/64bit, Server 2003/2008 32/64bit, 2008 R2/2012 64bit, Macintosh OS X 10.x, Unix/Linux/Citrix  Print fonts  80x PCL Latin, 137x PostScript 3, Emulation Latin  Print functions  Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)  "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed  Up to 80 opm Up to 80 opm Up to 80 opm Up to 80 opm (optional) (optional) (aptional)  R-ADF (300 dpi)  100 originals 100 originals 100 originals 100 originals  Scan speed Up to 80 opm/160 ipm Up to 80 o	Page description	PCL 6c (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS					
Macintosh OS X 10.x, Unix/Linux/Citrix  Print fonts  80x PCL Latin, 137x PostScript 3, Emulation Latin  Print functions  Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)  "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed  Up to 80 opm Up to 80 opm Up to 80 opm Optional) (optional) (optional) (optional)  R-ADF (300 dpi)  Dual scan (300 dpi)  100 originals  Automatic document feed  Paper weight automatic feeds  Scan resoluti  Max.: 600 x 600  Network TWAIN scan, scan-to-eMail (scan-to-Me), scan-to-FTP, Scan-to-SMB (scan-to-Home), scan-to-Box, scan-to-WebDAV, scan-to-DPWS, scan-to-USB	language						
Print fonts  BOx PCL Latin, 137x PostScript 3, Emulation Latin  Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)  "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed  Up to 80 opm Up to 80 opm Up to 80 opm - (optional)  R-ADF (300 dpi)  100 originals  100 originals  100 originals  100 originals  Scan speed Up to 80 opm/160 ipm	Operating system						
Print functions  Direct printing PCL, PS, TIFF, XPS, PDF and encrypted PDF files, Mixmedia and Mixplex, OOXML (DOCX, XLSX, PPTX)  "Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed  Up to 80 opm Up to 80 opm Up to 80 opm Ooptional) (optional) (optional) (optional)  R-ADF (300 dpi)  100 originals  100 originals  100 originals  Scan speed Up to 80 opm/160 ipm Up to 80							
"Easy Set" job planning, superimposition, watermark, copy protection  SCANNER  Scan speed Up to 80 opm Up to 80 opm Up to 80 opm (6/200 dpi) (optional) (optional) (optional) (optional) (optional)  R-ADF (300 dpi) 100 originals 100 originals 100 originals  Scan speed Up to 80 opm/160 ipm Up to 8	Print fonts	80x PCL Latin, 137x PostScript 3, Emulation Latin					
SCANNER Scan speed Up to 80 opm Up to 80 opm Up to 80 opm	Print functions						
Scan speed (B/W and colour)         Up to 80 opm (optional)         Up to 80 opm (optional)         Up to 80 opm (optional)         -		"Easy Set" job planning,	superimposition, waterma	rk, copy protection			
Scan speed Up to 80 opm Up to 80 opm Up to 80 opm	SCANNED						
(B/W and colour) (optional) (optional) (optional) (optional)  R-ADF (300 dpi) 100 originals 100 originals 100 originals  Scan speed Up to 80 opm/160 ipm Up		IIn to 90 onm	Un to 90 anm	Un to 90 anm			
R-ADF (300 dpi)  100 originals  Up to 80 opm/160 ipm Up t	•				-	-	
Scan speed Up to 80 opm/160 ipm Up to 80 opm/160 ip							
(B/W and colour) (optional) (optional) (optional) (standard) (standard)  Dual scan (300 dpi) 100 originals 100 originals 100 originals 100 originals 100 originals  Automatic document feed  Paper weight automatic feeds  Scan resoluti Max.: 600 x 600  Network TWAIN scan, scan-to-eMail (scan-to-Me), scan-to-FTP, Scan-to-SMB (scan-to-Home), scan-to-Box, scan-to-WebDAV, scan-to-DPWS, scan-to-USB					11s to 00 some /100 inco	Un to 00 anno /100 inno	
Dual scan (300 dpi)  100 originals	•						
Automatic document feed  Paper weight automatic feeds  Scan resoluti  Network TWAIN scan, scan-to-PWS, scan-to-USB  A6-ADF o Dualscan ADF  A6-AJF o Dualscan ADF	= = = = = = = = = = = = = = = = = = = =				,	,	
Feed Paper weight automatic Feeds Feeds Fean resoluti Scan modes Network TWAIN scan, scan-to-eMail (scan-to-Me), scan-to-FTP, Scan-to-SMB (scan-to-Home), scan-to-Box, scan-to-WebDAV, scan-to-DPWS, scan-to-USB			100 originals	100 originais	100 originals	100 originals	
Paper weight automatic feeds  Scan resoluti  Max.: 600 x 600  Network TWAIN scan, scan-to-eMail (scan-to-Me), scan-to-FTP, Scan-to-SMB (scan-to-Home), scan-to-Box, scan-to-WebDAV, scan-to-DPWS, scan-to-USB		K-ADF O Duaiscan ADF					
feeds Scan resoluti Max.: 600 x 600 Scan modes Network TWAIN scan, scan-to-eMail (scan-to-Me), scan-to-FTP, Scan-to-SMB (scan-to-Home), scan-to-Box, scan-to-WebDAV, scan-to-DPWS, scan-to-USB		Λ6 Λ2 2E 1C2?					
Scan resoluti Max.: 600 x 600 Scan modes Network TWAIN scan, scan-to-eMail (scan-to-Me), scan-to-FTP, Scan-to-SMB (scan-to-Home), scan-to-Box, scan-to-WebDAV, scan-to-DPWS, scan-to-USB		A0-A3, 33-163 gm²					
Scan modes Network TWAIN scan, scan-to-eMail (scan-to-Me), scan-to-FTP, Scan-to-SMB (scan-to-Home), scan-to-Box, scan-to-WebDAV, scan-to-DPWS, scan-to-USB		M C00 - C00					
scan-to-WebDAV, scan-to-DPWS, scan-to-USB							
	Scan modes						
					167 1) 34-5	. 1/26	

#### **FINISHER OPTIONS**

Scan outputs






2.100 (single + group), LDAP support







PPTX e PPTX searchable (optional), DOCX/XLSX searchable (optional)

















mixplex /



(10/13) - Code: 29020-01


OLIVETTI S.P.A. VIA JERVIS 77 10015 IVREA (TO) ITALY

www.olivetti.com

Performance refers to use of the product in optimal conditions. With the right to change technical characteristics. The registered trademarks are the property of their respective owners.

The d-Color MF222plus/MF282plus/MF362plus/MF452plus/MF552plus are distributed by Olivetti S.p.A.





<b>USER BOX SPECIFICATION</b>	
Max. box memory	Up to 3.000 documents or 10.000 pages
Types of user box	Public, private (with password or authentication), group (with authentication)
Types of system box	Secure printing, encrypted PDF printing, fax receipt, fax polling
Box functions	Re-print, combination, download, send (e-mail, FTP, SMB and fax), box-to-box copy

FAX			
Fax standard	Super G3 (optional)		
Fax trasmission	Analog, i-Fax, colour i-Fax (RFC3949-C), IP-Fax		
Fax resolution	Max. 600 x 600 (ultra-fine)		
Fax compression	MH, MR, MMR, JBIG		
Modem Fax	Up to 33,6		
Fax output	2.100 (single + group)		
Fay functions	Polling deferred transmission PC-Eav recention in private hoves recention via email/ETP/SMR, up to 400 inh programs		















### d-COLOR

MF222<sup>plus</sup> MF282<sup>plus</sup> MF362<sup>plus</sup> MF452<sup>plus</sup> MF552<sup>plus</sup>

Already finished..??? That's what users enjoying the benefits of the **new Olivetti colour products** will be asking. All the typical activities of the office workplace will be **smooth, fast** and personalisable. At the same time, thanks to compliance with the latest environmental impact regulations, attention will be firmly focused on eco-sustainability.



INNOVATIVE CONTROL PANEL WITH MULTI-TOUCH FUNCTIONS

REMOTE CONTROL PANEL

PRINT QUALITY UP TO 1200 x 1200 DPI WITHOUT LOSS OF SPEED

SUPPORT FOR SPECIAL SRA3 AND BANNER PAPER FORMATS

PDF/A PRODUCTION WITH OCR SUPPORT

DIRECT PRINTING AND SCANNING OF POWERPOINT, EXCEL, WORD DOC

2 GB RAM AND 250 GB HDD

**SLEEP MODE ENERGY CONSUMPTION 0.2 WATT** 

## d-COLOR MF222plus MF282plus MF362plus MF452plus MF552plus

#### CUTTING-EDGE PERFORMANCE WITH THE FOCUS ON SUSTAINABILITY

With the introduction of the new d-Color MF222plus/ 282plus/362plus/452plus/552plus, Olivetti enhances its A3 colour offer with a complete systems line ranging from 22 to 55 pages per minute and equipped with a series of new features to speed up machine-side activities and make user operations more flexible and fluid, while ensuring security. The systems can be configured in "kiosk" mode, giving access to pre-defined control panel screens where only the functions approved for the specific user account are available. These include **internet** browsing, direct printing and scanning, secure virtuous viewing of the 250 Gb HDD. Special care has also been devoted to the machines' environmental footprint and energy consumption, to offer users significant **cost savings** and ensure eco-sustainability. In compliance with the directives of the **new Energy Star 2.0** standard, the new line lowers energy consumption to 0.2 Watt in sleep mode and has Typical Energy Consumption (TEC) of 1.3/3.5 kWh/week, depending on the product.



9.5" multi-touch control panel with 10-key pad (optional)



Advanced security options, multiple authentication systems



#### CONTROL PANEL OR SMART PHONE?

The new A3 products are equipped with an **ultra-innovative 9" colour control panel** implementing new-generation **multi-touch technology**, to activate a series of functions typical of smart phones, such as a zoom and image rotation. Scrolling of machine functions and related screens is much more fluid thanks to the greater intuitiveness provided by real freedom of

The control panel is the gateway to the machine functions, guiding the user through document **creation/sharing/ archiving procedures.** The high-resolution screen also allows users to consult documents saved in the user box and to display a preview of the current document. Another important innovation is access to the **control panel from a remote tablet or PC**: a replica of the control panel appears on the remote workstation, to provide support or control the system settings.



Direct printing and scanning with USB, direct management of Microsoft Office formats

# acolomy.22\*\*\*


#### EXCELLENT FINISHING OPTIONS FOR PRODUCTION OF PROFESSIONAL DOCUMENTS

The advanced print functions of the new Olivetti models offer **fully automatic production of professional documents.** With a choice of 3 finishers, the user always has the ideal solution to turn out high-quality documents (brochures, flyers, presentations, course materials, etc.). Finisher functions can be enhanced with optional modules for **punching**, production of **booklets**, creation of **z-fold leaflets** or **insertion of covers**, as well as offset sorting.

#### UNLIMITED PRODUCTIVITY

The d-Color MF222plus/282plus/362plus/452plus/552plus are equipped with an internal print controller offering PCL6/PS3 emulation and XPS compatibility, to process the majority of document formats used in today's offices. They also **support Microsoft Office Open XML, to print and save** Microsoft Office docx, xlsx and pptx documents directly to and **from a USB pendrive.** Thanks to the internal web server, documents can also be saved/printed in cloud mode, **accessing archives resident** for example on a corporate **FTP.** Should PS3 emulation not be sufficient, a **Fiery option with native PS3** is available (not for the d-Color MF222plus) to optimise management of colour profiles and a full range of functions required by graphic artists.

#### **OPTIONS**



- \* Not available for MF222plus
- \*\* Also available for MF452plus
- \*\*\* Not compatible when the copier disk is installed \*\*\*\* Also available in an FS-534SD version (integrated SD 511)



d-Color MF552plus