

Cost-efficient and compact colour solutions



Aficio" MP C2030/MP C2530

Colour flexibility for all office types

The demands on office document production rise ever higher. Colour use is increasingly becoming a standard, but document outsourcing eats away at your budget. Ricoh's Aficio ™MP C2030/MP C2530 constitute a welcome alternative. Productive, flexible and compact, these colour MFPs offer excellent value for your money. Discover how all the capabilities you require can fit inside a slim design.

Superb colours Your colour output will look crisp and accurate due to the MP C2030/MP C2530's PxP[™] toner. Quality remains consistent even during longer runs. Print resolution is an excellent 600 dpi.

Excellent productivity Duplex printing at simplex speeds: not all machines can do it. The MP C2030/MP C2530 print and copy at 20/25 ppm in both monochrome and full colour. First copy speed is less than 6.5 seconds for B/W and less than 9.5 seconds for full colour.

- Sharp and high-quality colour output with new PxP™ toner.
- Excellent productivity at 20/25 ppm in both colour and B/W.
- Duplexing at simplex speed.

- · Exceptionally wide media handling.
- All-round functionality: copying, printing, scanning and faxing (optional).





1 One bin tray 2 Side tray 3 Standard 2 x 250-sheet paper trays 4 Optional 2 x 500-sheet paper trays

Wide media range Creating reports, handouts or flyers? The MP C2030/MP C2530 handle a truly wide variety of paper types. They accept sizes between A3 and A6, from light (52 g/m² via the bypass tray) to heavy (256 g/m² via standard and bypass trays). Glossy and coated papers or card stock are processed effortlessly. Even envelopes and transparencies can conveniently be fed via the standard bypass tray.

Standard printing capabilities The new MP C2030/MP C2530 have all basic printer features as standard. Enjoy their functionalities with the straightforward icon-based RPCS[™] driver, or with the optional PCL driver. Your B/W copies can even be sorted electronically for extra convenience.

Reliable engines The MP C2030/MP C2530's engines are the fruit of years of Ricoh expertise. Their new tandem 4-drums design ensures reliable operation. A simplified paper path reduces the risk of jams, and your machine is continuously available. With a maximum paper capacity of 1,600 sheets, refills are kept to a minimum.

We think green, and you? 'Green' is not just a colour for Ricoh – it is an attitude. Our PxP™ (polyester x polymerisation) toner is produced with significantly less carbon oxide emission than conventional toners. A more direct benefit for you is the MP C2030/MP C2530's standard duplex unit. Saving paper is kind to the environment as well as to the company budget.





◘₽7∞0

Specifications

Aficio[®] MP C2030/MP C2530

COPIER

Copying process:	Dry electrostatic transfer system
Copy speed:	MP C2030: B/W / full colour: 20 copies per minute MP C2530: B/W / full colour: 25 copies per minute
Resolution:	600 dpi
Multiple copy:	Up to 999
Warm-up time:	Less than 25 seconds ¹
First output speed:	Black and white: Less than 6.5 seconds Full colour: Less than 9.5 seconds
Zoom:	25 - 400% (in 1% steps)
Memory:	Standard: 512 MB
Paper input capacity:	Standard: 2 x 250-sheet paper trays, 1 x 100-sheet bypass tray Maximum: 1,600 sheets
Paper output capacity:	Maximum: 550 sheets
Paper size:	A6 - A3
Paper weight:	Paper tray 1: 60 - 256 g/m² Paper tray 2: 60 - 169 g/m² Bypass tray: 52 - 256 g/m² Duplex tray: 60 - 105 g/m²
Dimensions (W x D x H):	587 x 655 x 845 mm (with ARDF)
Weight:	Less than 100 kg (with ARDF)
Power source:	220 - 240 V, 50/60 Hz
Power consumption:	Operation: Maximum 1,680 W ¹

Print speed:	MP C2030: B/W / full colour: 20 prints per minute MP C2530: B/W / full colour: 25 prints per minute
Printer language:	Standard: RPCS™ Option: PCL5c, PCL6
Resolution:	600 dpi
Interface:	USB 2.0 Host
	USB 2.0 Device
	Ethernet 10 base-T/100 base-TX
Network protocol:	TCP/IP (IPv4, IPv6), IPX/SPX
Supported environments:	Windows 2000/XP/Vista/Server 2003/Server 2008 IBM iSeries
	AS/400 [®] using OS/400 Host Print Transform

ocari speca.	
Resolution:	
Original size:	
Bundled drivers:	

BW: 41 images per minute (LEF, A4) Full colour: 26 images per minute Maximum 600 dpi A5 - A3 TWAIN Network

SOFTWARE

SmartDeviceMonitor™ Web SmartDeviceMonitor™ Web Image Monitor DeskTopBinder™ Lite/Professional/v.5

(FAX (option)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Modem speed:	Maximum 33.6 Kbps
Resolution:	200 x 100/200 dpi
Compression method:	MH, MR, MMR, JBIG
Scanning speed:	36 sheets per minute
Memory capacity:	Standard: 4 MB
Memory backup:	Yes

OTHER OPTIONS

500-sheet paper tray, 2 x 500-sheet paper trays, Caster table, Cabinet, Inner one bin tray, Side tray, PCL module, Fax unit, Fax stamp ink, Copy Data Security Unit, PictBridge, Counter interface unit type A, Key counter bracket, Remote communication gate BN1

¹ Warm-up time and power consumption may differ depending on the conditions and environment of the machine.

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

For availability of models, optional apparatus and software, please consult your local Ricoh supplier.







Rb

Wiffi

 \bigcirc

🔏 PictBridge

ISO9001 certified ISO14001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2009 Ricoh Europe PLC.

All rights reserved. This brochure, its contents and/or layout may not be modified and/ or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.



www.ricoh-europe.com

For more information, please contact

Ricoh Uk Ltd 1 Plane Tree Crescent Feltham Middlesex TW13 7HG Tel.: +44 (0) 20 8261 4200 Fax: +44 (0) 20 8261 4288 www.ricob.co.uk

RICOH